



**DEWALT D25133K-B5**

## Heavy Duty SDS Plus Comb. Hammer, 26mm, 220V

**MODEL# D25133K-B5**

### FEATURES:

- Ideal for drilling anchor and fixing holes into concrete and masonry from 4 to 26 mm in diameter
- Rotation-stop for light chiseling applications in brick, soft masonry and occasionally concrete
- Impact-stop for drilling in wood, steel, ceramic and screw driving applications
- Mechanical clutch eliminates sudden high-torque reaction should the bit jam
- Electronic variable speed for total control in any application
- Ergonomic rubber coated back handle design for improved comfort in use
- Rounded ergonomic industrial design allows easy and comfortable handling in any application
- Improved sealing for maximum protection from dust ingress ensuring long tool life
- Output air slots designed to protect users' eye

### SPECIFICATIONS:

Power Input	800 Watts
No Load Speed	0-1500 rpm
Blows per Minute	0-5500 bpm
Impact energy (EPTA 05/2009)	2.6 J
Tool Holder	SDS-Plus
Max. Drilling Capacity [Wood]	30 mm
Max. Drilling Capacity [Metal]	13 mm
Max. Drilling Capacity [Concrete]	26 mm
Max. Drilling Capacity [Core bit]	50 mm
Weight	2.6 kg
Length	335 mm
Height	210 mm

Sound Pressure	89 dB(A)
Sound Pressure Uncertainty	3.8 dB(A)
Sound Power	100.1 dB(A)
Sound Power Uncertainty	3.8 dB(A)
Hand/Arm Vibration - Hammer drilling into concrete	15.4 m/s <sup>2</sup>
Hand/Arm Vibration – Chiselling	14.9 m/s <sup>2</sup>
Hand/Arm Vibration - Drilling into metal	<2.5 m/s <sup>2</sup>
Hand/Arm Vibration - Screw driving without impact	<2.5 m/s <sup>2</sup>
Uncertainty K 1 (Vibration)	1.5 m/s <sup>2</sup>