



DEWALT D25481K 40MM SDS MAX COMBINATION HAMMER W/AVC 5KG 220V

MODEL# D25481K

FEATURES:

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 40 mm in diameter. Core drilling up to 90 mm
- Chain drive improves durability and increases efficiency together with an oil-filled gearbox to ensure total component lubrication and superior heat dissipation
- Ergonomic; compact and slim line design maximizes control and offers easy access to confined spaces
- Excellent power to weight ratio: 8 Joules of impact energy delivered by a 6.1 kg hammer
- Rotation-stop for medium-light demolition applications
- Unique dust sealing protection to prevent even the finest dust ingress into the hammer mechanism delivering high durability and extended tool life
- Hammer mechanism is optimized by reducing the number of components and by improving dampening to deliver maximum impact energy and therefore the efficiency to drill into the hardest concrete
- Efficient mechanism delivers impact blows directly to the bit without losses through excessive vibration and rebound dampening reduces stress to the tool
- Soft rubber grip handles improve user comfort lowering fatigue during extended use



SPECIFICATIONS:

- Tool Holder: SDS-Max
- Power Input: 1100 Watts
- Power Output: 500 Watt
- Impact energy (EPTA 05/2009): 8 J
- Load Speed: 400 rpm
- Blows per Minute: 2740 bpm
- Max. Drilling Capacity [Concrete]: 40 mm
- Max. Drilling Capacity [Breakthrough bit]: 55 mm
- Max. Drilling Capacity [Core bit]: 90 mm
- Weight: 6.1 kg
- Length: 457 mm
- Height: 245 mm
- Width: 104 mm
- Hand/Arm Vibration –
Hammer drilling into concrete: 18.3 m/s²
- Uncertainty K 1 (Vibration): 1.8 m/s²
- Hand/Arm Vibration – Chiseling: 13.2 m/s²
- Uncertainty K 2 (Vibration): 1.6 m/s²
- Sound Pressure: 94 dB(A)
- Sound Pressure Uncertainty: 3 dB(A)
- Sound Power: 104 dB(A)
- Sound Power Uncertainty: 3 dB(A)

INCLUDED:

- Side Handle
- Carry Case